



Water-proofing HQ (OL108)

Fighting humidity and weathering is very simple, with this Ambro-Sol Water-proofing silicon you'll give a durable protection to surfaces and materials. All this without trace of odour and colour.



HOW TO USE: Use the product in a ventilated place. Shake before use. Clean the surface to be treated (the surface must be clean and dry) Apply the product uniformly from a distance of 30 cm approx. For a best results, we recommend repeating the treatment after a few hours.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0° degrees and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

Hazards identification:

H222	Extremely flammable aerosol.
H229	Pressurized container: may burst if heated
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
EUH066	Repeated exposure may cause skin dryness or cracking

This information, even if reliable, must be considered only approximate. The usage don't imply our responsibility, included the violation of many license. Before using, the users have to verify the suitability of the product for the specific use

Quantity	500 ml
Barcode	EAN 13: 8034108891729
Confection	12 pz

WATER-PROOFING HQ – High-performance silicon for plastic industry, rubber and cut. Colorless, odorless, solvent free, it works from -40° C to +250° C. Protective, lubricant, releasing, waterproof for each type of material, excellent for many functions. It can also be used in boating, camping and in the house.

Technical Specifications:

Aspect	Cylinder containing under pressure fluid
Color	Transparent
Odour	Characteristic of solvent
Relative density	a 20°C 0,65 ÷ 0,69 g/ml
Flash point	Low.0° C
Pressure at 20°C	4/6 bar
PH	÷ 6
Solid content	20% c.a.
Viscosità	> 1,00 mPa.s.
Solubility	Partially soluble in water
Operating temperature	-40°C – +250°C